
Subject: use of Terminal Emulator II
Posted by [sfk](#) on Mon, 03 Jun 2013 03:14:21 GMT
[View Forum Message](#) <> [Reply to Message](#)

Message-ID:
Date: Wed, 6-Feb-85 19:15:29 EST
Article-I.D.: wucs.710
Posted: Wed Feb 6 19:15:29 1985
Date-Received: Thu, 7-Feb-85 04:29:08 EST
Organization: Washington U. in St. Louis, CS Dept.
Lines: 22

I am having trouble getting Terminal Emulator II to work. I have a terminal that is set with no parity, 1 stop bit, and 8 data bits. I set the TE-II with no parity, but the others I can't choose. Even so, I should at least get some garbage sent, but I am not able to send or receive anything (the transmit light on the modem doesn't light when I type something). I am able to send to and receive from the terminal in BASIC when I connect it to the RS232 card, but if I connect the modem instead, again I get no response. Any suggestions?

Thanks in advance.

Steve Karasek

--

Steven Karasek sfk@wucs.UUCP
Box 1045 Washington University (ihnp4!wucs!sfk)
St. Louis, MO 63130 USA (314)-889-5098

--

Steven Karasek sfk@wucs.UUCP
Box 1045 Washington University (ihnp4!wucs!sfk)
St. Louis, MO 63130 USA (314)-889-5098