
Subject: Re: 2400 takeapart advice/experience
Posted by [Alex Santos](#) on Wed, 31 Dec 2014 19:36:10 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Andrew

Thanks for chiming back, I am attempting a reset between seeing your message and writing this. I will report back. So far, I can only hear a very short pop, tick sound coming from the speaker after holding the reset for the 10 20 seconds as per <http://support.apple.com/ja-jp/HT1781>

One little correction, the CPU card, connected towards the bottom of the logic board is not what I thought should have an EMI shield, I was looking at the cardbus cage. Sorry for any confusion.

I discovered that one does not have to totally take-apart the 2400c. With the machine facing you, it's enough to disconnect the PRAM battery. Once the logic board is exposed J11 is the PRAM connector. J7 is the speaker. J9, which is just above J11 I am unable to determine as to its use.

Are there schematics for 2400c anywhere?

--
--

You received this message because you are a member of the PowerBooks list, a group for those using pre-G3 PowerBooks.

The list FAQ is at <http://lowendmac.com/lists/powerbooks.shtml> and our netiquette guide is at <http://www.lowendmac.com/lists/netiquette.shtml>

To post to this group, send email to powerbooks@googlegroups.com

To leave this group, send email to powerbooks+unsubscribe@googlegroups.com

For more options, visit this group at <http://groups.google.com/group/powerbooks>

You received this message because you are subscribed to the Google Groups "PowerBooks" group.

To unsubscribe from this group and stop receiving emails from it, send an email to powerbooks+unsubscribe@googlegroups.com.

For more options, visit <https://groups.google.com/d/optout>.